



240

Husqvarna 240 is ideal for jobs like pruning, lighter cutting tasks and hobby work. Easy to start and operate, thanks to built-in Husqvarna features like ergonomic design, facilitating technology and powerful X-Torq® engine with low emissions.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



COMBINED CHOKE/STOP CONTROL

Combined choke/stop control allow for easier starting and reduce the risk of engine flooding.



SIDE-MOUNTED CHAIN TENSIONER

Side-mounted chain tensioner makes chain adjustment quick and easy.

Features

- LowVib® sparing the user's arms and hands
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	2.3 cu.inch / 38.2 cm ³
Power output	2 hp / 1.5 kW
Maximum power speed	9000 rpm
Idling speed	3000 rpm
Spark plug	Champion RCJ7Y
Electrode gap	0.02" / 0.5 mm
Oil tank volume	0.09 US pint / 0.2 lit
Oil pump type	Fixed flow
Equivalent vibration level (ahv, eq) front / rear handle	2.1/2.7 m/s ²
Sound pressure level at operators ear	100.7 dB(A)
Sound power level, guaranteed (LWA)	113 dB(A)
Chain pitch	.325" / 3/8"
Recommended bar length, min-max	13"-16" / 33-40 cm
Chain speed at max power	53.48 fts / 16.3 m/s
Chain speed at 133% of maximum engine power speed	71.19 fts / 21.7 m/s
Weight (excl. cutting equipment)	10.3 lbs / 4.7 kg

ARTICLES

952 80 21-54	16" - 3/8 - SN - EPA - US, CA
967 17 71-01	14" - 3/8"

