



HD 5.0/50 Ec Cage

This cold water electric pressure washer in a roll cage design is built for durability and power. These industrial-stength machines deliver up to 5.0 GPM at 5,000 PSI.

TECHNICAL DATA AND EQUIPMENT



HD 5.0/50 Ec Cage

Technical data		
Order no.		1.107-087.0
EAN code		4039784453852
Current type	Ph / V / Hz	3 / 460 / 60
Working pressure	PSI	5000
Equipment		
ANTI!Twist		-
Pressure switch-off		-
Servo control		-

















		Order no.	Max. working pressure	Length		Price	Description
Rotating spray lances							,
Spray lance	1	4.760-660.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.
	2	4.760-664.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.
	3	4.760-663.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.
	4	4.760-661.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.
	5	4.760-662.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.
Spray lance							
250 mm lance, non-rotatable	6	4.760-667.0		250 mm			250 mm stainless steel lance. With manual coupling. Non-rotatable. $\hfill\Box$
Flexible spray lance							
High pressure articulated joint	7	4.481-039.0	300 bar				High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer.

[■] Included in the scope of supply.

Available accessories.









		1		1		1		_
		Order no.	Flow rate			Price	Description	
Trigger guns		'	•	'	'			
High-end HP trigger gun	1	4.775-823.0					High-end spray guns with optimised flow. Small pressure losses also with water volumes up to 2500 l/h. Robustness and durability for professional use. Food-safe and saltwater-resistant materials offer the best conditions for use in the food sector and in industry. Connector for HP hoses M 22 × 1.5.	
Quick connect								
Quick coupling	2	6.401-458.0					For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.	
Male coupling	3	6.401-459.0					Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 x 1.5 external thread.	

[■] Included in the scope of supply.

Available accessories.





		Order no.	Nozzle size		Price	Description
Power nozzle spray angle 25°						
Chemical nozzle	1	2.884-521.0	250			Brass power nozzle for low pressure operation and cleaning agent suction. $\hfill\Box$

[■] Included in the scope of supply.

□ Available accessories.



















		1	1	1			
		Order no.	ID	Max. working	Length	Price	Description
		order no.	10	pressore	Length	FIICE	Description
Standard with unions on both sides	5						
High-pressure hose, 10 m, ID 8, 315 bar, extension	1	6.391-342.0	DN 8	315 bar	10 m		To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5.
Longlife 400							
High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun con- nection	2	6.391-351.0	DN 8	400 bar	10 m		With patented AVS connection in the trigger gun (rotatable) and hand screw connection, M 22 x 1.5 with kink protection. ☐ With double steel reinforcement.
Longlife 400 with unions on both s	ides						
High-pressure hose 1.5 m, ID 8, including connectors	3	6.390-178.0	DN 8	400 bar	1.5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).
High-pressure hose Longlife 400, 10 m, ID 8, extension	4	6.391-354.0	DN 8	400 bar	10 m		To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5.
High-pressure hose Longlife 400, 15 m, ID 8, including rotary cou- pling	5	6.389-709.0	DN 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5
Longlife food design with screw co	nnectio	ons at both ends					
High pressure hose food ID 8, 10 m	6	6.391-864.0	DN 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding mate-
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	7	6.391-887.0	DN 8	400 bar	20 m		rial. With rotary coupling, 2 x M 22 x 1,5
Special hoses							
High-pressure hose, 1.5 m, ID 8, incl. connection parts, curved outflow	8	6.388-886.0	DN 8	400 bar	1.5 m		Connection hose in longlife quality with 2x M22 x 1.5, with angled connection on one side.

[■] Included in the scope of supply.

Available accessories.





		Order no.			Price	Description	
Rotary coupling							
Rotary coupling	1	4.401-091.0				Reliably prevents twisting of HP hoses. Connection M 22 x 1.5 m. Handle protection	

[■] Included in the scope of supply.

□ Available accessories.





		Order no.	Max. working pressure	Nozzle size	Diame- ter	Price	Description
Drum and tank cleaning							
Add-on kit mud sucker	1	2.641-798.0					For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.

[■] Included in the scope of supply.

Available accessories.