

Fleet Wash Detergent

SDS Number: K803724

Revision Date: June 30, 2017

Page 1 of 5

1	PRODUCT AND COMPANY IDENTIFICATION
----------	---

Product Name: Fleet Wash Detergent
Revision Date: June 30, 2017
Version: 46-53D
SDS Number: K803724

Manufactured for: Canadian Contact:

Kärcher North America
 4555 Airport Way
 Denver, CO 80239
 Phone: 303-738-2400
 Email: info@karcherna.com

Kärcher North America
 6535 Millcreek Drive, Unit 67
 Mississauga, ON L5N 2M2
 Phone: 905-672-8233

Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500

2	HAZARDS IDENTIFICATION
----------	-------------------------------

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

- Health, Acute toxicity, 4 Oral
- Health, Skin corrosion/irritation, 1 C
- Health, Serious Eye Damage/Eye Irritation, 1

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

- H302 - Harmful if swallowed
- H314 - Causes severe skin burns and eye damage
- H318 - Causes serious eye damage

GHS Precautionary Statements:

- P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 - Wash thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P363 - Wash contaminated clothing before reuse.

Fleet Wash Detergent

SDS Number: K803724

Revision Date: June 30, 2017



Page 2 of 5

Route of Entry: Eyes, Skin, Inhalation:
Target Organs: Eyes; Skin; Respiratory system;
Inhalation: Can cause irritation and inflammation of the respiratory tract.
Skin Contact: Irritating to skin; may cause burns, blisters and itching.
Eye Contact: Irritating to eyes, eye damage may occur.
Ingestion: Irritating to intestinal tract; may cause burns, vomiting, stomach pain, and disorientation.

NFPA: Health = 2, Fire = 1, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 2, Fire = 1, Physical Hazard = 0

HMIS PPE: C - Safety Glasses, Gloves, Apron



3 COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
6834-92-0	4%	Sodium metasilicate
111-76-2	3%	Ethylene Glycol Butyl Ether
27176-87-0	2%	Sulfonic Acid DDBSA

OSHA Regulatory Status:

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

4 FIRST AID MEASURES

Inhalation: Remove from exposure and get fresh air. Keep warm and at rest. Get medical attention immediately if artificial respiration is required.

Skin Contact: Remove contaminated clothing, jewelry and shoes immediately. Flush affected area with large amounts of water, then use soap or mild detergent and large amounts of water for 15-20 minutes to cleanse area. If skin is severely irritated or burned, get medical attention immediately.

Eye Contact: Immediately flush eyes with large amounts of water occasionally lifting upper and lower lids for at least 15 minutes. Get immediate medical attention.

Ingestion: Rinse mouth with water. DO NOT INDUCE VOMITING unless instructed to by medical personnel. If vomiting occurs keep head lower than hips to help prevent aspiration. If person is unconscious, do not induce vomiting; turn their head to the side. Never make an unconscious person vomit or drink fluids. Get medical attention.

Fleet Wash Detergent

SDS Number: K803724

Revision Date: June 30, 2017

Page 3 of 5

5	FIRE FIGHTING MEASURES
----------	-------------------------------

Flash Point: 100 ° C / 212 ° F
Flash Point Method: Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6	ACCIDENTAL RELEASE MEASURES
----------	------------------------------------

Isolate area; keep unnecessary personnel away. Do not discharge into drains. Ventilate closed spaces before entering. Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. Wear appropriate protective equipment and clothing during cleanup. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7	HANDLING AND STORAGE
----------	-----------------------------

Handling Precautions: Do not get in eyes, on skin, or on clothing. Do not breathe vapor. Keep container closed. Promptly clean up spills. Wash thoroughly after handling.

Storage Requirements: Store out of reach of children; keep container closed; store in a cool, well-ventilated place.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
----------	--

Engineering Controls: Normal room ventilation is satisfactory for limited use.
Personal Protective Equipment: HMIS PP, C | Safety Glasses, Gloves, Apron

Ethylene glycol butyl ether 111-76-2 OSHA PEL 50 ppm - 240 mg/m3

Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

9	PHYSICAL AND CHEMICAL PROPERTIES
----------	---

Appearance:	Clear kelly green	Odor:	Fresh scent
Physical State:	Liquid	Solubility:	Soluble
Spec Grav./Density:	8.84 lb/gallon		
pH:	12.94 as is, 11.45 at 5% solution		

10	STABILITY AND REACTIVITY
-----------	---------------------------------

Chemical Stability: Product is stable under normal conditions.
Conditions to Avoid: None known
Materials to Avoid: Strong oxidizing or acidic materials
Hazardous Decomposition: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
Hazardous Polymerization: Will not occur.

Fleet Wash Detergent

SDS Number: K803724

Revision Date: June 30, 2017

Page 4 of 5

11	TOXICOLOGICAL INFORMATION
-----------	----------------------------------

Sodium Metasilicate 6834-92-0

Oral (LD 50): 1153 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Severe

Eye irritation: Severe

Sensitization: Not considered an occupational sensitizer

Ethylene glycol butyl ether 111-76-2

Oral (LD 50): 917 mg/kg - Rat

Inhalation (LC 50): 2900 mg/m³/7H - Rat

Skin irritation: Mild

Eye irritation: Mild

Sensitization: Not considered an occupational sensitizer

Sulfonic Acid DDBSA 27176-87-0

Oral (LD 50): 650 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Severe

Eye irritation: Severe

Sensitization: Not considered an occupational sensitizer

12	ECOLOGICAL INFORMATION
-----------	-------------------------------

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13	DISPOSAL CONSIDERATIONS
-----------	--------------------------------

Recommendation: Consult with the disposal agency and the relevant authorities. Empty containers may be cleaned with water.

14	TRANSPORT INFORMATION
-----------	------------------------------

UN1760, Corrosive liquids, n.o.s., 8, PGIII, (Sodium metasilicate)

Ship in accordance with 49 CFR parts 100-185.

Fleet Wash Detergent

SDS Number: K803724

Revision Date: June 30, 2017

Page 5 of 5

15

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Sodium metasilicate (6834-92-0) [4%] TSCA, WHMIS

Ethylene Glycol Butyl Ether (111-76-2) [3%] MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

Sulfonic Acid DDBSA (27176-87-0) [2%] CERCLA, CSWHS, MASS, PA, TSCA, WHMIS

Regulatory CODE Descriptions

All components are listed on TSCA

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

MASS = MA Massachusetts Hazardous Substances List

OSHA = OSHA workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

WHMIS = workplace Haz Mat Info Sys Canada

16

OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager