

This hot water pressure washer contains an electric boiler for use where exhaust gases need to be avoided. It is efficient and eco-friendly, with energy savings up to 40%.

















1 Especially high work temperature

- Large hot water tank (max. 85 °C).
- Up to 45 °C in continuous operation under full load or 70 °C with servo control.

3 Mobility concept

- Jogger" design with large wheels and castors.
- $\hfill \blacksquare$ For easy tilting when negotiating obstacles such as steps and kerbs.

2 Highly energy efficient, for high cost savings


■ Highly effective insulating material saves up to 40 % energy in standby mode.

4 Operating concept

- Storage hooks for power cord and high-pressure hose.
- Central control panel with service indicators.

TECHNICAL DATA AND EQUIPMENT





HDS-E 3.3/25-4M Ec

■ Economical eco!efficiency mode

Technical data		
Water Volume	GPM	1,6 / 3,3
Operating pressure	PSI	465 / 2520
Connected load	Α	48
Power rating	hp	7,5
Weight	lbs	423
Dimensions (L x W x H)	in	52,5 × 29,5 × 41,5
Power supply	Ph / V / Hz	3 / 460 / 60

Equipment				
Anti-twist system (AVS)		-	Scale inhibitor	
Three piston axial pump		with ceramic piston	Service control	•
Stainless steel spray lance	in	41	Control panel with indicator lamps	•
Trigger gun		Easy-press trigger gun	Two detergent tanks	•
High-pressure hose	ft	50	Switch-CHEM-System	•
Pressure switch control		-		
Trigger gun with soft grip		•		
Dry run protection				
Low-speed 4-pole motor				
Power nozzle				
SDS system				
■ Included in delivery				

Included in delivery.















		Order no.	ID		Length	RRP	Description
Standard with unions on both sides							
High-pressure hose packaged	1	6.391-342.0	ID 8	315 bar	10 m		A
Longlife 400 with unions on both si	des						
High-pressure hose packaged	2	6.391-354.0	ID 8	400 bar	10 m		A
Longlife food design with screw cor	nnectio	ons at both ends					
High pressure hose food DN 8 / 10 m	3	6.391-864.0	ID 8	400 bar	10 m		A
High-pressure hose food industry 400 bar, 20 m, DN 8, including rotary coupling	4	6.391-887.0	ID 8	400 bar	20 m		A
Longlife 400							
High-pressure hose packaged	5	6.391-351.0	ID 8	400 bar	10 m		
Special hoses							
High-pressure hose 1.5 m, DN 8, including connectors, outlet bend	6	6.388-886.0	ID 8	400 bar	1,5 m		

[■] Included in delivery.

Available accessories.

Extension hose.





















		1	1		1	1		
		Order no.		Length			RRP	Description
Rotating spray lances								
1050 mm lance, rotatable, ergono- mic	1	4.760-660.0	300 bar	1050 mm				_
Rotatable lance, 600 mm, ergono- mic	2	4.760-664.0	300 bar	600 mm				
Lance 850 mm, rotatable, ergono- mic	3	4.760-663.0	300 bar	840 mm				
Lance 1550 mm, rotatable, ergo- nomic	4	4.760-661.0	300 bar	1550 mm				
Lance 2050 mm, rotatable, ergo- nomic	5	4.760-662.0	300 bar	2050 mm				
Spray lances								
Anti-vibration lance	6	6.415-951.0	250 bar	950 mm				
Spray lance								
Lance 250 mm, non-rotatable	7	4.760-667.0		250 mm				
Double lance								
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm				
Telescopic spray lance								
Strap for telescopic spray pipe	9	6.373-987.0						

[■] Included in delivery.

Available accessories.

Extension hose.





					Diame-		
		Order no.	Water Volume	Nozzle size	ter	RRP	Description
Hard surface cleaner FRV 30							
Add-on kit rubber lip	1	2.642-910.0					
Flächenreiniger FR 50 Me							
FRV 50 ME	2	2.643-598.0					

[■] Included in delivery.

Available accessories.

Extension hose.







		Order no.	Water Volume		RRP	Description
Trigger guns						
High end high-pressure trigger gun	1	4.775-823.0				
Quick connect						
Quick coupling	2	6.401-458.0				
Plug nipple	3	6.401-459.0				

[■] Included in delivery.

Available accessories.

Extension hose.





		Order no.	Nozzle size		RRP	Description	
Power nozzle spray angle 25°							
25° power nozzle for applying cleaning agent	1	2.884-521.0	250				

[■] Included in delivery.

Available accessories.

Extension hose.







		Order no.			RRP	Description
Coupling parts		Order no.			RRP	Description
Coupling parts		6.987-705.0			RRP	Description
Coupling parts Rotary coupling					RRP	
Coupling parts					RRP	Description

[■] Included in delivery.

Available accessories.

Extension hose.





			 		 		_
		Order no.	Nozzle size	Diame- ter	RRP	Description	
Pipe cleaning nozzle							1
Pipe cleaning dirt blaster D 25 / 060	1	6.415-945.0	60	25 mm			
Pipe cleaning dirt blaster D 30 / 060	2	6.415-947.0	60	30 mm			
Pipe cleaning dirt blaster D 35 / 060	3	6.415-949.0	60	35 mm			

[■] Included in delivery.

Available accessories.

Extension hose.







		Order no.	Length		RRP	Description
Automatic, self-winding hose reels						
Add-on kit hose reel plastics	1	6.392-975.0	20 m			
Add-on kit hose reel	2	6.392-965.0	20 m			

[■] Included in delivery.

Available accessories.

Extension hose.











		Order no.	Water Volume	Water feed temperature	Length	Length	RRP	Description
Solar cleaning - telescopic lances		'	•	1				
iSolar TL 7 H (without hose)	1	4.107-054.0		60 °C				
Telescopic rod complete 10m	2	4.107-053.0		60 °C				
Telescopic rod complete 10m CFK	3	4.107-055.0		60 °C				
Telescopic rod complete 14m	4	4.107-052.0		60 °C				
Hose solar	5	6.392-978.0		155 ℃				
	6	6.392-977.0		155 ℃				
	7	6.392-976.0		155 ℃				

[■] Included in delivery.

Available accessories.

Extension hose.