



140U

Forestry mulcher for special built hydraulic or PTO driven Prime Movers with power range between 80 and 180 HP.

Standard equipment: single trasmission (for 125, 150 and 140), double side transmission (for 200 and 225), hydraulic hood, adjustable skids.

Options: customized hydraulic or PTO transmission, pushing frame, hydraulic pushing frame, customized attachment plate, teeth on hydraulic hood, possibility to have the rotor equipped with tooth type "C/SD" or type "D".



140U - PTO

Model	Tractor HP min max	PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty type C+C/SS
140/U - 125 - PTO	80 - 130	1000	53	64	3087	10	26+2
140/U - 150 - PTO	80 - 130	1000	62	73	3307	10	32+2

140U - HY

Model	Power HP Min - Max	Requirements Flow gal/min Min - Max	Pressure PSI Min - Max	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty type C+C/SS
140/U - 140 - HY	80 - 150	40 - 65	3500 - 5000	58	69	2866	10	30+2
140/U - 200 - HY	110 - 180	80 - 90	3500 - 5000	81	95	3594	10	42+2
140/U - 225 - HY	110 - 180	80 - 90	3500 - 5000	91	105	3902	10	48+2

The data refers to the machine without options.



Tooth type C (standard)



Tooth type C/SD (option)



Tooth type D (option)



Tooth type C/SS (side scraper)