TRACTOR PULL MIXERS SD Series MAJOR COMPONENTS



Aggressive Knife



Curved Knife



Triangle Knife

All Tornado Augers are equipped with 3 different styles of deep serrated, heat treated, tungsten carbide knives. 3 different style of knives depending on your nutrition needs can process any kind of fiber (hay, haylage, silage, straw, byproducts, corn and soybean stalks).

SD 2 Speed Gearbox



SD Tornado Auger

Auger Thickness 1/2"

(Option 3/4")

Hiway Commercial Low Pro



Super Singles



Hiway Commercial Dual Tires

SD Planetary Gearbox 3-5 yr warranty



SD Walking Axlå (Optional)

SD Dual Conveyor



SD Frame Component



SD Flip-up Conveyor



Bolt on Double Entry Safe Viewing Platform (Optional)



TRACTOR PULL MIXERS SD Series

Model 4020 S.D. Low Pro Trailer Base Machine






Standard Equipment: Corner Door




	4020
Single Auger	Y
Capacity (Top of Metal) cu/ft	400
cu/metre	11,3
Capacity (with Extension) cu/ft	470
cu/metre	13,3
Trailer Model	Y
Truck Mount	Y
Stationary Model	Y
540 RPM	Std.
1000 RPM	Opt.
No 2 - Speed Gearbox (HP)	80
1:3 Regular 2 - Speed Gearbox (4020 SD - 60 HP / 5020 SD - 80 HP)	Opt.
1:5 Low 2 - Speed Gearbox (4020 SD - 60 HP / 5020 SD - 75 HP)	Opt.
1:8 Super Low 2 - Speed Gearbox (4020 SD - 50 HP / 5020 SD - 70 HP)	Opt.
Corner Door-Right Front	Opt.
Left Rear	Opt.
Dual Conveyor	Opt.
Sliding Dual Conveyor	Opt.
Dog Leg Conveyor (Right or Left Side)	Opt.
Flip-up Conveyor (Right or Left Side)	Opt.
Rear Commodity Door	Opt.
Extra Side Door(s)	Opt.
Weight-Pounds	6 693
Kilograms	3 036
Single Axle	Std.
26 X 12 on 6 Bolt	Opt.
12.5L X 15 on 8 Bolt Rims	N/A
19/45X17 Flotation on 8 Bolt Rims	Std.
245/70/17.5 Duals on 8 Bolt	Opt.
245/70RX19.5 Duals on 10 Bolt Rims	N/A
435/50R/19.5 Super Singles	Opt.
500/45X20 Lugger on 10 Bolt Rims	N/A
Brakes	Opt.
Lights	Opt.
Thickness Wall - 1/4", Floor - 1/2"	

Options: Flip-up Conveyor (Right Side)



Options: Flip-up Conveyor (Left Side)



Options: Dual Conveyor

