

Unverferth®



Ripper-Roller

Tillage Tool



**Shatter hardpan,
incorporate residue and
level the surface to minimize
pre-plant tillage trips.**

*** /nnovative design • Q uality manufacturing**



Deep ripping with unmatched leveling for high-residue environments

The model 630 features auto-reset shanks with 6,000 pounds of trip pressure that pivot upward and rearward upon contact with rocks and other infield obstacles. The model 610 features shear-bolt protected shanks with 7,500 pounds of shear pressure. All-welded steel construction and 6"x6" rear toolbar provide exceptional structural strength and years of durability.

The Ripper-Roller's lead coulter's feature a 6-bolt hub and 20" ripple blade that cuts through the heaviest corn, cotton, rice, wheat and other high-volume residues for maximum flow.

They're followed by steep-sloped shanks that till up to 18" deep for thoroughly mixing the soil. Shanks are staggered 28" for reduced horsepower requirements and are spaced 18" apart for optimum residue flow. They feature invertible 1 1/4"-wide triangular-shaped wearbars for extended life and easier pulling.

The shanks are followed by your choice of two leveling options:

- A 16" roller with beveled, high-carbon steel blades that shatter clods, chop and help distribute residue, or
- A 13" diameter cleated roller with 3" tall spiraled drive lugs propel the roller for maximum leveling and firming action.



Available with cleated roller for maximum firming and leveling in low-residue applications

All rollers feature dual, heavy-duty 3"x3" spring-cushioned mounting arms on each section for fine-tuning the soil finish. Independent mounting allows each section to closely follow ground contour and flex up and over obstacles.



Available 16" roller with high-carbon steel blades to shatter larger clods, chop and help distribute residue

Other Ripper-Roller options include angle-adjustable shatter wings for shanks for greater fracturing of the soil, shark fin points for less surface disruption and a lighting kit for safer nighttime road travel.

The Unverferth Ripper-Roller tillage tool is available in 7-, 9-, 11- and 13-row rigid models. They feature a high-quality, powder-coat finish of tractor red or green that resists corrosion. Standard stabilizer wheels with new 7.60 x 15 tires provide consistent depth control and stability.

Ripper-Roller Specifications

Number of shanks	Shank spacing	Transport Width	Model 630	Model 610
			Appx. wt. (lbs) with cleated rolling finisher	
7	18"	11'4"	4,600	3,750
9	18"	13'10"	5,800	4,465
11	18"	16'6"	6,850	6,035
13	18"	19'	7,975	7,055

For complete details about the Ripper-Roller tillage tool, see your nearest Unverferth dealer today, check our Web site at www.unverferth.com or call 1-800-322-6301.



®.TM Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, Ohio

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada

© 2009 Unverferth Manufacturing Co., Inc. Printed in U. S. A.



P.O. Box 357 • Kalida, Ohio 45853
(419) 532-3121 • FAX (419) 532-2468

unverferth.com
1-800-322-6301



Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Mfg. Co., Inc. supports the efforts of Farm Safety 4 Just Kids and all organizations that promote farm safety.