

NEW

UMM/DT

Forestry mulcher with fixed teeth rotor for tractors between 140 and 240 HP.

Standard equipment: PTO driveshaft with cam clutch, gearbox with freewheel, self-ranging system of the PTO drive shaft gearbox type "Z", hydraulic rear hood, centralized greasing hub, adjustable skids, interchangeable counter blades and inner plates screwed from outside.

Options: mechanic or hydraulic guard frame, available with extra ripper teeth, special skids to go underground, W-style self-aligning device between gearbox and PTO, possibility to have the rotor equipped with tooth type C/3/HD or type STCL/3.

Notes: For the correct usage, creeper gear transmission and reversible driving console are recommended.



UMM/DT

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type C/3+C/3/SS
	min	max						
UMM/DT 200	100	240	1000	2070	2470	2180	300	42+2
UMM/DT 225	110	240	1000	2310	2710	2430	300	46+2
UMM/DT 250	120	240	1000	2550	2950	2500	300	52+2

Data refers to the machine without options.



Tooth type C/3 (standard)



Tooth type C/3/HD (option)



Tooth blade type C/3 (option)



Tooth type STCL/3 (option)



Tooth type C/3/SS (side scraper)