

1435 SERIES SPLIT WING DISC HARROWS



37'-3" & 40'-0"
Working widths



13'-6"
Transport height



18'-2"
Transport width



"Split-Wing"
Technology
(patented)

1435 SPLIT WING FEATURES

- Aggressive over-lapping front gangs
- Ridge eliminating staggered rear gangs
- Full concavity 22" (559 mm.) or 24" (610 mm.) disc blades
- 8.75" (222 mm) blade spacing
- Patented split-wing folding system
- Greaseless UHMW hinges and transport connections
- 1 3/4" (44.5 mm) alloy steel disc gang shaft
- C-Flex™ mounted trunnion disc gang bearings
- Walking tandems at all locations
- 2.75" (69.9 mm.) center section hubs with 8 bolt wheels
- C-Flex mounted scraper bars
- Parallel linkage mounted swivel gauge wheels
- Long heavy-duty tongue with wide set mountings
- Single-point depth control
- Self-leveling system
- Welded heavy-duty frame
- 3-year limited warranty



Cuts through tough residue with over 225 lbs. (102 kg) of weight per blade

13'- 6" TRANSPORT HEIGHT SIMPLE AS - 1 - 2 - 3



1. Complete the fold sequence



2. Install the transport locks



3. Lower the tool to retract wing lift cylinders

1435 SERIES SPLIT WING DISC HARROWS

MODEL NUMBER	WORKING WIDTH ft. (m.)	TRANSPORT WIDTH ft. (m.)	TRANSPORT HEIGHT * ft. (m.)	WEIGHT lbs. (kg.)	NUMBER OF BLADES front/rear	WEIGHT PER BLADE lbs. (kg.)	WEIGHT PER FOOT lbs. (kg.)
1435-37SW	37-3 (11.35)	18-2 (5.54)	13-6 (4.11)	23,978 (10,876)	52/54	226 (102.51)	644 (292.12)
1435-40SW	40-0 (12.19)	18-2 (5.54)	13-6 (4.11)	24,590 (11,154)	56/58	216 (97.98)	615 (278.85)

* Transport height attained with fully retracted wing lift cylinders.

FOR MORE INFORMATION:
1-800-748-8481 • (785) 738-2261 • FAX (785) 738-2406
Internet - www.sunflowermfg.com • E-mail - sales@sunflowermfg.com

SUNFLOWER

Sunflower Manufacturing Co., Inc.
P.O. Box 566 • 3154 Hallie Trail • Beloit, KS 67420