

Fertilizer Applicator

MODEL	1860
Tank size	1800 US gallon tank, stainless steel baffle, hopper bottom sump w/ 3" fill
Tool bar	- Available in 24/30" (25), 36/20" (37), 36/22" (37), 18/38" (19) widths - Active hydraulic down pressure. - Four (4) gauge wheels. - Double 5 x 7 mainframe with ground contour following wing sections
Tire size	Dual tire 380/90R54, 320/90R54 Single tire/rim 380/90R54
Wheel spacing	60"/120", 80"/120", 88"/132", 76"/152" Duals 120", 132" Single tire
Plumbing	- Ace hydraulic driven centrifugal pump kit. - 5 section control valves - Raven 450 rate controller
Coulters	20" ripple, spring-cushioned Knives or injectors Hydraulic depth control assist
Ground clearance	36" in field operation, 54" on turn rows
Transport width	18' 6"
Transport height	13' 6"
Transport length	24' 3"
Hitch pin to axle length	185"
Fresh water safety tank	9 gallon
Quick fill	3"
Empty weight ¹	20,100 lbs
Tongue weight, transport	1,520 lbs
Tongue weight, field	5,380 lbs

¹ Approximate measurement

MODEL	2460
Tank size	2400 US gallon tank, stainless steel baffle, hopper bottom sump w/ 3" fill
Tool bar	- Available in 24/30" (25), 36/20" (37), 36/22" (37), 18/38" (19) widths - Active hydraulic down pressure. - Four (4) gauge wheels. - Double 5 x 7 mainframe with ground contour following wing sections
Tire size	Dual tire 380/90R54, 320/90R54
Wheel spacing	60"/120", 80"/120", 88"/132", 76"/152" Duals
Plumbing	- Ace hydraulic driven centrifugal pump kit. - 5 section control valves - Raven 450 rate controller
Coulters	20" ripple, spring-cushioned Knives or injectors Hydraulic depth control assist
Ground clearance	36" in field operation, 54" on turn rows
Transport width	18' 6"
Transport height	13' 6"
Transport length	24' 3"
Hitch pin to axle length	185"
Fresh water safety tank	9 gallon
Quick fill	3"
Empty weight ¹	20,100 lbs
Tongue weight, transport	1,520 lbs
Tongue weight, field	5,380 lbs

¹ Approximate measurement