

# SNOWBLOWERS

# Farm King

For tractors 15 hp to 225 hp

Hydraulic Snowblowers | PTO Snowblowers




**FARM KING HAS BEEN BUILDING RELIABLE AGRICULTURAL AND COMMERCIAL SNOWBLOWERS FOR MORE THAN FOUR DECADES.**


The design has stood the test of time through the years, while continuously refined to create the best line of snowblowers in the industry. The new Propeller blade from Farm King is the culmination of that expertise and experience.

**WHAT SETS THE PROPELLER APART IS THE AGGRESSIVE BLADES ON A PADDLE-STYLE AUGER THAT MAXIMIZES PERFORMANCE IN EXTREME CONDITIONS WITH HEAVY, PACKED AND WET SNOW.**

The rapid rotation of the auger with the propeller blades breaks down larger pieces of snow as it enters the machine and moves toward the fan, providing a smoother flow of snow into the fan.

Farm King Snowblowers are available in sizes ranging from 50" widths and up. Heavy-duty widths are also available ranging from 96" to 120".





**THE ALLIED BY FARM KING BINARY SNOWBLOWER OFFERS TWO IMPLEMENTS IN ONE MACHINE.**

Farmers are making the most of their equipment assets and the new Allied by Farm King Hydraulic Snowblower offers the flexibility to be used on a skid steer or a tractor with a PTO and 3-point hitch. By removing a few bolts and changing some hardware, the hydraulic snowblower can be used on a traditional farm tractor. Allied by Farm King Binary Snowblowers are available in sizes ranging from 50" to 84" widths.

| SPECIFICATIONS            |                            |                  |                            |                  |                            |                  |                            |                  |                            |                  |
|---------------------------|----------------------------|------------------|----------------------------|------------------|----------------------------|------------------|----------------------------|------------------|----------------------------|------------------|
| MODEL                     | H500                       |                  | H600                       |                  | H660                       |                  | H740                       |                  | H840                       |                  |
|                           | Standard                   | High             | Standard                   | High             | Standard                   | High             | Standard                   | High             | Standard                   | High             |
| Hydraulic flow            |                            |                  |                            |                  |                            |                  |                            |                  |                            |                  |
| Cutting width             | 50"                        |                  | 60"                        |                  | 66"                        |                  | 74"                        |                  | 84"                        |                  |
| Cutting height            | 24"                        |                  | 24"                        |                  | 24"                        |                  | 25"                        |                  | 25"                        |                  |
| Cutting edge              | Replaceable opt.           |                  | Replaceable opt.           |                  | Replaceable opt.           |                  | Replaceable opt.           |                  | Replaceable opt.           |                  |
| Mount plate               | Universal                  |                  | Universal                  |                  | Universal                  |                  | Universal                  |                  | Universal                  |                  |
| Hydraulic requirements    | 17-23 gpm                  | 23-26 gpm        | 17-23 gpm                  | 23-26 gpm        | 17-23 gpm                  | 23-26 gpm        | 17-23 gpm                  | 23-26 gpm        | 17-23 gpm                  | 23-26 gpm        |
| Hydraulic horsepower, max | 44 hp @ 3300 PSI           | 69 hp @ 3300 PSI | 44 hp @ 3300 PSI           | 69 hp @ 3300 PSI | 44 hp @ 3300 PSI           | 69 hp @ 3300 PSI | 44 hp @ 3300 PSI           | 69 hp @ 3300 PSI | 44 hp @ 3300 PSI           | 69 hp @ 3300 PSI |
| Fan speed, max            | 664 RPM                    | 699 RPM          | 664 RPM                    | 699 RPM          | 664 RPM                    | 699 RPM          | 664 RPM                    | 699 RPM          | 664 RPM                    | 699 RPM          |
| Fan torque, max           | 3350 ft-lb                 | 521 ft-lb        | 3350 ft-lb                 | 521 ft-lb        | 3350 ft-lb                 | 521 ft-lb        | 3350 ft-lb                 | 521 ft-lb        | 3350 ft-lb                 | 521 ft-lb        |
| Fan                       | 4 blade                    |                  | 4 blade                    |                  | 4 blade                    |                  | 4 blade                    |                  | 4 blade                    |                  |
| Fan diameter              | 22"                        |                  | 22"                        |                  | 22"                        |                  | 23"                        |                  | 23"                        |                  |
| Fan drive motor           | 8.0 cuin                   | 11.9 cuin        | 8.0 cuin                   | 11.9 cuin        | 8.0 cuin                   | 11.9 cuin        | 8.0 cuin                   | 11.9 cuin        | 8.0 cuin                   | 11.9 cuin        |
| Fan drive                 | #80 Chain                  | #80HS            | #80 Chain                  | #80HS            | #80 Chain                  | #80HS            | #80 Chain                  | #80HS            | #80 Chain                  | #80HS            |
| Auger diameter            | 15"                        |                  | 15"                        |                  | 15"                        |                  | 15"                        |                  | 15"                        |                  |
| Auger drive               | #50 Chain                  |                  | #50 Chain                  |                  | #50 Chain                  |                  | #50 Chain                  |                  | #50 Chain                  |                  |
| Chute rotation            | Hydraulic 270°             |                  | Hydraulic 270°             |                  | Hydraulic 270°             |                  | Hydraulic 270°             |                  | Hydraulic 270°             |                  |
| Chute deflector           | Hydraulic                  |                  | Hydraulic                  |                  | Hydraulic                  |                  | Hydraulic                  |                  | Hydraulic                  |                  |
| Skid shoes                | Adjustable and replaceable |                  | Adjustable and replaceable |                  | Adjustable and replaceable |                  | Adjustable and replaceable |                  | Adjustable and replaceable |                  |
| Weight                    | 480 lb                     |                  | 528 lb                     |                  | 573 lb                     |                  | 814 lb                     |                  | 906 lb                     |                  |



# SNOWBLOWER

Compact Models 500, 600, 660, 740, 840

## SNOWBLOWER

### PRODUCT OVERVIEW

Rear attach for use on acreages, farms and municipalities

Category I, II, IIIN

15 - 90 hp

### FEATURES

Spout rotator and deflector available as manual or hydraulic

Standard shear bolt protection on all PTOs

### OPTIONS

Electric spout rotator (models 500, 600, 660 only)

### AVAILABLE COLORS\*



\*Red is the standard color.

## FARM KING HAS BEEN BUILDING RELIABLE SNOWBLOWERS FOR MORE THAN THREE DECADES.

Through the years the design has been refined to create an excellent snowblower that is easy to use and maintain. PTO-driven Farm King compact snowblowers attach to 3-point hitch and are available in widths ranging from 50" to 84".

The Farm King snowblower features a hand crank or hydraulic spout rotator on models 500, 600 and 660. A hydraulic cylinder is standard on the spout rotation on models 740 and 840.



**Model 500** - 50" (1.3 m) cutting width  
For tractors 15 - 30 hp, 3-point hitch Category I

**Model 600** - 60" (1.5 m) cutting width  
For tractors 20 - 40 hp, 3-point hitch Category I

**Model 660** - 66" (1.7 m) cutting width  
For tractors 22 - 40 hp, 3-point hitch Category I

**Model 740** - 74" (1.9 m) cutting width  
For tractors 40 - 70 hp, 3-point hitch Category I / II

**Model 840** - 84" (2.1 m) cutting width  
For tractors 60 - 90 hp, 3-point hitch Category I / II / IIIN

**[1]** A hand crank spout rotator is standard on models 500, 600 and 660 while a hydraulic setup is standard on models 740 and 840 **[2]** Adjustable and replaceable skid shoes are standard equipment **[3]** The chain drive is easily accessible for routine maintenance **[4]** The open gear setup is easy to maintain and service.



#### SPECIFICATIONS

| MODEL >>   | 500                                    | 600                                    | 660                                    | 740                                 | 840   | 840G  |
|--|--|--|--|-------------------------------------|---|---|
| Cutting width  | 50"                                    | 60"                                    | 66"                                    | 74"                                 | 84"   | 84"   |
| Cutting height   | 24"                                    | 24"                                    | 24"                                    | 25"                                 | 25"   | 25"   |
| Replaceable cutting edge   | N/A                                    | N/A                                    | N/A                                    | N/A                                 | N/A   | N/A   |
| Fan  | 4-blade                                | 4-blade                                | 4-blade                                | 4-blade                             | 4-blade   | 4-blade   |
| Fan dimensions   | 22" x 7"                               | 22" x 7"                               | 22" x 7"                               | 23" x 7"                            | 23" x 7"  | 23" x 7"  |
| Replaceable fan housing  | N/A                                    | N/A                                    | N/A                                    | N/A                                 | N/A   | N/A   |
| Drive fan  | 540 RPM<br>open gear                   | 540 RPM<br>open gear                   | 540 RPM<br>open gear                   | 540 RPM<br>open gear                | 540 RPM<br>open gear  | 540 RPM<br>oil bath gearbox                                 |
| Auger diameter   | 15"                                    | 15"                                    | 15"                                    | 15"                                 | 15"   | 15"   |
| Auger drive  | #50 chain                              | #50 chain                              | #50 chain                              | #50 chain                           | #50 chain   | #50 chain   |
| Spout rotator<br>- manual (hand crank)<br>- hydraulic cylinder   | Standard<br>Optional                   | Standard<br>Optional                   | Standard<br>Optional                   | N/A<br>Standard                     | N/A<br>Standard   | N/A<br>Standard   |
| Spout deflector<br>- manual (6 position)<br>- hydraulic cylinder | Standard<br>Optional                   | Standard<br>Optional                   | Standard<br>Optional                   | Standard<br>Optional                | Standard<br>Optional  | Standard<br>Optional  |
| Skid shoes   | Adjustable and<br>replaceable          | Adjustable and<br>replaceable          | Adjustable and<br>replaceable          | Adjustable and<br>replaceable       | Adjustable and<br>replaceable                               | Adjustable and<br>replaceable                               |
| Hitch category   | Cat. I standard<br>Cat. I Q.H standard | Cat. I standard<br>Cat. I Q.H standard | Cat. I standard<br>Cat. I Q.H standard | Cat. I standard<br>Cat. II bushings | Cat. I & II std<br>Cat. II Q.H. std<br>Cat. III Q.H. narrow | Cat. I & II std<br>Cat. II Q.H. std<br>Cat. III Q.H. narrow |
| Hitch adjustment   | 4 position                             | 4 position                             | 4 position                             | 2 position                          | 2 position  | 2 position  |
| Tractor requirement  | 15 - 30 hp                             | 20 - 40 hp                             | 22 - 40 hp                             | 40 - 70 hp                          | 60 - 90 hp  | 60 - 90 hp  |
| Weight   | 422 lb                                 | 470 lb                                 | 515 lb                                 | 756 lb                              | 848 lb  | 878 lb  |



# SNOWBLOWER

Models 960, 1080, 1200

## SNOWBLOWER

### PRODUCT OVERVIEW

Rear attach for use on acreages, farms and municipalities

Category II, III

90 - 225 hp

### FEATURES

Spout rotator and deflector available as manual or hydraulic

Standard shear bolt protection on all PTOs

### OPTIONS

Commercial and truck loader chute, 1080 & 1200 models

### AVAILABLE COLORS\*



\*Red is the standard color.

## FARM KING SNOWBLOWERS ARE BUILT TO WORK HARD FOR MANY WINTERS TO COME.

Designed to be durable and rugged, Farm King Snowblowers offer excellent value in a snowblower that will stand the test of time. These heavy-duty snowblowers are available in widths ranging from 96" to 120".

The Farm King snowblower utilizes a powerful hydraulic motor to control the spout rotation. Using a motor to control rotation increases the blower's responsiveness and gives the operator a greater range of control over the placement of the snow. Standard on all heavy-duty models, a hand crank optional is available on model 960.



**Model 960** - 96" (2.4 m) cutting width, 3-point hitch Category II / III  
For tractors 90 - 125 hp

**Model 1080** - 108" (2.7 m) cutting width, 3-point hitch Category II / III  
For tractors 120 - 180 hp


**Model 1200** - 120" (3 m) cutting width, 3-point hitch Category II / III  
For tractors 180 - 225 hp

### HEAVY WEIGHTED

With weights ranging from 1,243 lb to 2,600 lb Farm King Snowblowers are among the heaviest in their class, built with heavy-gauge steel to enhance durability. The gearbox is housed in a sealed oil bath that is resistant to heat, moisture and debris.

The PTO and sprocket to the main auger are protected from damage by shear bolts.

**[1]** Dual 15" augers work with a 4-blade fan to pull snow through quickly and evenly **[2]** A 7' or 10.5' commercial truck loader chutes are optional on the 1080 and 1200 models **[3]** Models 960, 1080 and 1200 utilize a powerful hydraulic motor to control the spout rotation **[4]** The hydraulically controlled hood deflector on the 1080 and 1200 provides for quick and simple adjustments on the fly.



### SPECIFICATIONS

| MODEL >>   | 960   | 1080   | 1200   |
|--|---|--|--|
| Cutting width  | 96"   | 108"   | 120"   |
| Cutting height   | 36"   | 41"  | 41"  |
| Replaceable cutting edge   | Optional  | Yes  | Yes  |
| Fan  | 4-blade   | 4-blade  | 4-blade  |
| Fan dimensions   | 32" x 9"  | 34" x 12"  | 34" x 12"  |
| Replaceable fan housing  | N/A   | 7 gauge  | 7 gauge  |
| Drive fan  | 540 RPM<br>oil bath gearbox                             | 1000 RPM<br>oil bath                                     | 1000 RPM<br>oil bath                                     |
| Auger diameter   | 15" (dual)  | 15" (dual)   | 15" (dual)   |
| Auger drive  | #60 chain   | #80 chain  | #80 chain  |
| Spout rotator<br>- manual (hand crank)<br>- hydraulic motor      | Optional<br>Standard                                    | N/A<br>Standard  | N/A<br>Standard  |
| Spout deflector<br>- manual (6 position)<br>- hydraulic cylinder | Standard<br>Optional                                    | N/A<br>Standard  | N/A<br>Standard  |
| Skid shoes   | Adjustable and<br>replaceable                           | Adjustable and<br>replaceable                            | Adjustable and<br>replaceable                            |
| Hitch category   | Cat. II std<br>Cat. II Q.H. std<br>Cat. III Q.H. narrow | Cat. II std<br>Cat. III Q.H. std<br>Cat. III Q.H. narrow | Cat. II std<br>Cat. III Q.H. std<br>Cat. III Q.H. narrow |
| Hitch adjustment   | Fixed   | 2 position   | 2 position   |
| Tractor requirement  | 90 - 125 hp   | 120 - 180 hp   | 180 - 225 hp   |
| Weight   | 1243 lb   | 2398 lb  | 2600 lb  |

## HD HYDRAULIC SNOWBLOWER

### PRODUCT OVERVIEW

Built for skid steer attachment

Widths range from 60" to 84"

17 to 40 GPM

### FEATURES

All components are hydraulically driven

Replaceable cutting edge

Adjustable skid shoes are standard

Heavy-gauge steel

### OPTIONS

6" width extenders



## HD HYDRAULIC SNOWBLOWER

Models 6025, 7225, 7235, 8425, 8435



### HYDRAULIC MOTOR CHAIN DRIVE ASSEMBLY

With a hood turning range of 270° Allied by Farm King HD Hydraulic Snowblowers give you superior control when moving snow.

### WIRING HARNESS

The Allied by Farm King HD Hydraulic Snowblower series have a wiring harness to fit almost any brand on the market. Compatibility available with: Bobcat 14, pin ASV, Cat "B / C / D" series 8 pin, Case / New Holland 14 pin and

John Deere 14 pin. A magnetic cab mounted control box is available on all other models.

### HYDRAULIC MOTORS

Allied by Farm King HD Hydraulic Snowblowers have hydraulic motors mounted directly on the fan and auger shaft eliminating couplers and chain drive assemblies for simplicity and ease of maintenance. A hydraulic relief replaces traditional shear pin technology for increased productivity and reduced downtime.





**THE ALLIED BY FARM KING HD HYDRAULIC SNOWBLOWERS HAVE BEEN ENGINEERED TO MAXIMIZE YOUR SKID STEERS EFFICIENCY.**

Available in high and standard flow configurations, Allied by Farm King blowers will connect with any modern skid steer. Designed to be durable and reliable, Allied by Farm King products are the best choice for industrial and commercial snow removal.



**[1]** Hydraulic motor chain drive. **[2]** Wiring harness fits most skid steer brands. **[3]** A hydraulic motor mounts directly on the fan and auger shaft eliminating couplers and chain drive assembly.

**SPECIFICATIONS**

| MODEL >>               | 6025                       | 7225                       | 7235                       | 8425                       | 8435                       |
|------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| Cutting width          | 60"                        | 72"                        | 72"                        | 84"                        | 84"                        |
| Cutting height         | 25"                        | 25"                        | 35"                        | 25"                        | 35"                        |
| Mount plate            | Universal                  | Universal                  | Universal                  | Universal                  | Universal                  |
| Hydraulic requirements | 17 - 23 GPM                | 17 - 23 GPM                | 32 - 40 GPM                | 17 - 23 GPM                | 32 - 40 GPM                |
| Throwing distance      | Up to 40'                  | Up to 40'                  | Up to 40'                  | Up to 40'                  | Up to 40'                  |
| Fan                    | 4-blade                    | 4-blade                    | 4-blade                    | 4-blade                    | 4-blade                    |
| Fan diameter           | 20"                        | 20"                        | 24"                        | 20"                        | 24"                        |
| Auger diameter         | 14"                        | 14"                        | 18"                        | 14"                        | 18"                        |
| Drive auger            | Hydraulic motor            | Hydraulic motor            | Hydraulic motor            | Hydraulic motor            | Hydraulic motor            |
| Chute rotation         | 270°                       | 270°                       | 270°                       | 270°                       | 270°                       |
| Chute deflector        | Hydraulic                  | Hydraulic                  | Hydraulic                  | Hydraulic                  | Hydraulic                  |
| Cutting edge           | ½" x 4" bolt-on            | ½" x 4" bolt-on            | ½" x 4" bolt-on            | ½" x 4" bolt-on            | ½" x 4" bolt-on            |
| Skid shoes             | Adjustable and replaceable | Adjustable and replaceable | Adjustable and replaceable | Adjustable and replaceable | Adjustable and replaceable |
| Weight                 | 828 lb                     | 923 lb                     | 1084 lb                    | 951 lb                     | 1108 lb                    |

## SNOWBLOWER

### PRODUCT OVERVIEW

Rear attach for use on acreages, farms and municipalities

Category I, II & III

15 - 225 hp required

### FEATURES

Spout rotator and deflector available as manual or hydraulic

Standard shear bolts on all PTOs

### OPTIONS

Commercial and truck loader chute, model 1080 and 1200



# SNOWBLOWER

5010, 6010, 6610, 7420, 8420, 9620, 1080, 1200



## SPOUT DEFLECTOR

The spout deflector can be equipped with a hydraulic cylinder kit or a 6-position manual adjustment.

## HITCH

Most models feature an adjustable hitch that is designed to adapt to 3-point hitches of varying lengths and heights, which reduces stress on the PTO shaft.

## GEARBOX

The oil bath gearbox, available on 84", 96", 108" and 1200 models, adds longevity.

## FAN

A 4-blade fan is standard on all models. Dual augers are standard on model widths 96" to 120".

## SPOUT ROTATOR

The spout rotator is available with manual or hydraulic positioning.

## SKID SHOES

Adjustable/replaceable skid shoes are standard on all models.



## ALLIED HAS BEEN BUILDING RELIABLE SNOWBLOWERS FOR MORE THAN THREE DECADES.

Through the years the design has been refined to create an excellent snowblower that is easy to use and maintain. PTO-driven Allied snowblowers attach to 3-point hitch and are available in widths ranging from 50" to 120".

**[1]** #50, #60 or #80 sized chain dependant on model **[2]** Dual augers **[3]** 7 foot commercial and 10 foot truck loading chutes are optional on the 1080 and 1200 models. **[4]** Binary models available in widths of 50-84"; Propeller models available in all models.



### SPECIFICATIONS

| MODEL >>  | 5010                       | 6010                 | 6610                 | 7420   | 8420   | 8420G  | 9620   | 1080  | 1200  |
|---|----------------------------|----------------------|----------------------|--|--|--|--|---|---|
| Cutting width / height                                  | 50" / 25"                  | 60" / 25"            | 66" / 24"            | 74" / 25"  | 84" / 25"  | 84" / 25"  | 96" / 36"  | 108" / 41"  | 120" / 41"  |
| Replaceable cutting edge                                | N/A                        | N/A                  | N/A                  | N/A  | N/A  | N/A  | Optional   | Yes   | Yes   |
| Fan type / diameter                                     | 4-blade / 22"              | 4-blade / 22"        | 4-blade / 22"        | 4-blade / 23"  | 4-blade / 23"  | 4-blade / 23"  | 4-blade / 32"  | 4-blade / 36"   | 4-blade / 36"   |
| Replaceable fan housing                                 | N/A                        | N/A                  | N/A                  | N/A  | N/A  | N/A  | N/A  | 7 gauge   | 7 gauge   |
| Drive fan   | 540 rpm open gear          |                      |                      |  |  | 540 rpm oil bath gearbox                                   |  | 1000 rpm oil bath gearbox                                   |   |
| Auger diameter  | 15"                        | 15"                  | 15"                  | 15"  | 15"  | 15"  | 15" (dual)   | 15" (dual)  | 15" (dual)  |
| Auger drive   | #50 chain                  | #50 chain            | #50 chain            | #50 chain  | #50 chain  | #50 chain  | #60 chain  | #80 chain   | #80 chain   |
| Spout rotator<br>- manual (hand crank)<br>- hydraulic   | Standard<br>Optional       | Standard<br>Optional | Standard<br>Optional | Optional<br>Standard   | Optional<br>Standard                                       | Optional<br>Standard                                       | Optional<br>Standard   | N/A<br>Standard   | N/A<br>Standard   |
| Spout deflector<br>- manual (6 position)<br>- hydraulic | Standard<br>Optional       | Standard<br>Optional | Standard<br>Optional | Standard<br>Optional   | Standard<br>Optional                                       | Standard<br>Optional                                       | Standard<br>Optional   | N/A<br>Standard   | N/A<br>Standard   |
| Skid shoes  | Adjustable and replaceable |                      |                      |  |  |  |  |   |   |
| Hitch category  | Cat. I standard            | Cat. I standard      | Cat. I standard      | Cat. I standard<br>Cat. II bushings<br>Cat. I & II heavy<br>frame optional | Cat. II std<br>Cat. II Q.H. std<br>Cat. III Q.H.<br>narrow | Cat. II std<br>Cat. II Q.H. std<br>Cat. III Q.H.<br>narrow | Cat. I & II std<br>Cat. II Q.H. std<br>Cat. III Q.H.<br>narrow | Cat. II std<br>Cat. III Q.H. std<br>Cat. III Q.H.<br>narrow | Cat. II std<br>Cat. III Q.H. std<br>Cat. III Q.H.<br>narrow |
| Hitch adjustment  | 4 position                 | 4 position           | 4 position           | 2 position   | 2 position   | 2 position   | Fixed  | 2 position  | 2 position  |
| HP requirement  | 15 - 30 hp                 | 20 - 40 hp           | 22 - 40 hp           | 40 - 70 hp   | 60 - 90 hp   | 60 - 90 hp   | 90 - 125 hp  | 120 - 180 hp  | 180 - 225 hp  |
| Weight  | 422 lb                     | 470 lb               | 515 lb               | 756 lb   | 848 lb   | 878 lb   | 1243 lb  | 2398 lb   | 2600 lb   |

[www.farm-king.com](http://www.farm-king.com)



# Farm King

**For more information contact:**

E-mail: [info@buhler.com](mailto:info@buhler.com)

[www.farm-king.com](http://www.farm-king.com)

Equipment shown is subject to change without notice. ©2015 Buhler Trading Inc.  
Printed in Canada. TSX:BUI Ref: 022016-3000-LM P/N: PSBLOWER

**bühler** | *a division of Buhler Industries Inc.*