

Square Bale Carrier

MODEL	4480
Capacity	GVW 25,000 lb (11,340 kg) 48" x 48" (122 x 122 cm) bales: 8, single row on carrier, stacked 4 high unloaded 32" x 35" (81 x 90 cm) bales: 20, double row on carrier, stacked 5 high unloaded 36" x 48" (91 x 122 cm) bales: 16, double row on carrier, stacked 4 high unloaded
Tractor requirements	100 hp (75 kW) at 16,700 lb (7,575 kg) Maximum recommended transport speed when loaded is 20 mph (32 km/hr)
Control	In cab control for complete manual and automatic operation. Includes hand-held control for convenient operation
Hand held remote control	12VDC, 15 amp circuit
Hydraulics	Tractor: one double acting remote valve required Lift: one, 4" DIA x 18" stroke cylinder Squeeze: one, 3" DIA x 16" stroke cylinder Rotate: one, 3" DIA x 16" stroke cylinder Tilt: two, 3.5" DIA x 36" stroke cylinder Pusher: two, 22.2 cu. in hydraulic motors
Tires	8, 12.5L x 15FI tires, load range F, intermittent unloaded highway
Tires, capacity	4,680 lb (2,130 kg) at 90 PSI inflation
Tires, hub	6 bolt with twine guard
Tires, wheel	Heavy-duty implement style
Deck length	34' (10.4 m)
Overall length	42.66' (13 m)
Transportation width	10.16' (3.1 m)
Shipping weight	9,485 lb (4,302 kg)