

Binary Snowblower

MODEL	H500		H600		H660		H740		H840	
	Standard	High	Standard	High	Standard	High	Standard	High	Standard	High
Cutting width	50"		60"		66"		74"		84"	
Cutting height	24"		24"		24"		25"		25"	
Cutting edge	Replaceable opt.		Replaceable opt.		Replaceable opt.		Replaceable opt.		Replaceable opt.	
Mount plate	Universal		Universal		Universal		Universal		Universal	
Hydraulic requirements	17-23 gpm	23-26 gpm	17-23 gpm	23-26 gpm	17-23 gpm	23-26 gpm	17-23 gpm	23-26 gpm	17-23 gpm	23-26 gpm
Hydraulic horsepower, max	44 hp @ 3300 PSI	69 hp @ 3300 PSI	44 hp @ 3300 PSI	69 hp @ 3300 PSI	44 hp @ 3300 PSI	69 hp @ 3300 PSI	44 hp @ 3300 PSI	69 hp @ 3300 PSI	44 hp @ 3300 PSI	69 hp @ 3300 PSI
Fan speed, max	664 RPM	699 RPM	664 RPM	699 RPM	664 RPM	699 RPM	664 RPM	699 RPM	664 RPM	699 RPM
Fan torque, max	3350 ft-lb	521 ft-lb	3350 ft-lb	521 ft-lb	3350 ft-lb	521 ft-lb	3350 ft-lb	521 ft-lb	3350 ft-lb	521 ft-lb
Fan	4 blade		4 blade		4 blade		4 blade		4 blade	
Fan diameter	22"		22"		22"		23"		23"	
Fan drive motor	8.0 cuin	11.9 cuin	8.0 cuin	11.9 cuin	8.0 cuin	11.9 cuin	8.0 cuin	11.9 cuin	8.0 cuin	11.9 cuin
Fan drive	#80 Chain	#80HS	#80 Chain	#80HS	#80 Chain	#80HS	#80 Chain	#80HS	#80 Chain	#80HS
Auger diameter	15"		15"		15"		15"		15"	
Auger drive	#50 Chain		#50 Chain		#50 Chain		#50 Chain		#50 Chain	
Chute rotation	Hydraulic 270°		Hydraulic 270°		Hydraulic 270°		Hydraulic 270°		Hydraulic 270°	
Chute deflector	Hydraulic		Hydraulic		Hydraulic		Hydraulic		Hydraulic	
Skid shoes	Adjustable and replaceable		Adjustable and replaceable		Adjustable and replaceable		Adjustable and replaceable		Adjustable and replaceable	
Weight	480 lb		528 lb		573 lb		814 lb		906 lb	