

WR401 HEAVY-DUTY WHEEL RAKE





	WR401	
DIMENSIONS		
Transport Width	12 ft. 3 in. (3.7 m)	
Transport Length	28 ft. 3 in. (8.6 m)	
Overall Height	90 in. (2.3 m)	
Maximum Raking width	30 ft. 3 in. (9.2 m)	
Maximum Windrow Width	72 in. (1.8 m)	
WEIGHT		
Shipping	5960 lbs. (2703 kg)	
Operating	5700 lbs. (2586 kg)	
RAKING COMPONENTS		
Number of Raking Wheels	17 Raking Wheels w/UV Resistant Panels	
Wheel Diameter	60 in. (1.5 m)	
Raking Teeth per Wheel	36 Rubber Mounted teeth in sets of 2	
Raking Wheel Support	Tapered Roller Bearings	
FRAME COMPONENTS		
Design	4 X 6 in. (102 X 152 mm) Telescoping Horizontal Members	
	Inside 5 x 7 in. (127 x 178 mm) Fixed Center Members	
	5 x 5 in. (127 x 127 mm) Vertical Members	
	3 x 5 in. (76 x 127 mm) Raking Wheel Beams	
Transport Axles	Offset Walking Beam	
Transport Tires	Four 9.5L x 15 SL Implement Tread	
Maximum Transport Speed	20 mph (32 k/h)	
ADJUSTMENTS		
Frame/Raking Wheel Beam Pitch	Ratchet Jack	
Raking Wheel Angle From Vertical	0 to 10 degrees	
Raking Wheel Ground Pressure	Independent at each Raking Wheel	
Transport Locks	Mechanical	
Tractor-Mounted Control Box	Independent Control of Rake Wings	
	Independent Control of Frame Width	
	Independent Control of Rake Wheel Raise/Lower	

TRACTOR REQUIREMENTS	
Hydraulic Remotes Required	1
Minimum Pressure Requirement	2000 psi (138 bar)
Standard 7-Pin Outlet	Required
Minimum Tractor HP Recommended	65 HP (49 kW)

STANDARD EQUIPMENT	
Hitch Jack	
Safety Chains	
Adjustable Clevis Hitch	
Brake/Turn/Tail Lights	
Work Light	
SMV Emblem	

OPTIONAL EQUIPMENT

Ball Hitch



Safety Never Hurts!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

Case IH is a registered trademark of CNH America LLC.

Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Availability of some models and equipment builds vary according to the country in which the equipment is used.