## ×

## **EU7000is**

- Electronic Fuel Injection (reduces maintenance associated with carburetors and fuel storage issues)
- 7000 Watts (45.8/22.9 A) 120/240 VAC of Honda inverter power
- Super Quiet 60 dB(A)
- . Large capacity fuel tank, 19.2 litres
- Eco-Throttle™ standard Runs up to 12.1 hours at ½ load on 19.2 litres of fuel
- Convenient Electric Start with Push button Switch (battery included) and Recoil as back-up
- Wheel Kit Standard with Positive Lock Folding Handle
- Perfect for a variety of tasks at home, work or outdoor events and for cottage or home backup power



YES

| SPECIFICATIONS                           |                                |  |  |
|--|--------------------------------|--|--|
| GENERATOR TYPE                           | DUAL INVERTER                  | REMOTE START KIT PART NUMBER INFO          | TBA  |
| MAXIMUM AC OUTPUT (WATTS)                | 7000                           | FUEL TANK CAPACITY (LITRES)                | 19.2                                       |
| VAC VOLTAGE AVAILABLE                    | 120 / 240                      | TRANSPORT WHEELS                           | 2-WHEEL KIT STD.                           |
| MAXIMUM CONTINUOUS AC OUTPUT (WATTS)     | 5500                           | LIFTING HOOK                               | OPTIONAL (P/N 06531-Z11-E00ZA)             |
| MAX. RATED AC AMPERAGE @ 120 V / 240 V   | 45.8 / 22.9                    | BATTERY                                    | STD. (P/N 31500-MCR-D02)                   |
| GROUND FAULT CIRCUIT INTERRUPTER (GFCI)  | N/A                            | APPROXIMATE RUNNING TIME / TANKFUL (HRS.)  | 6.6**/18 ***                               |
| FREQUENCY (HERTZ)                        | 60                             | RATED FUEL CONSUMPTION (LITRES / HOUR)     | 2.9**                                      |
| VOLTAGE REGULATION SYSTEM                | PWM (Pulse Width Modulation)   |  |  |
| DC OUTPUT (VOLTS / AMPS)                 | N/A                            | NOISE LEVEL dB(A) (1.5 METRES TO 7 METRES) | 60**                                       |
| Honda ENGINE                             | GX390T2                        | LENGTH                                     | N/A  |
| ТҮРЕ                                     | OHV; 4-STROKE; AIR-COOLED      | LENGTH - WITH HANDLES FOLDED               | 848 mm (33.4 in.)                          |
| DISPLACEMENT                             | 389 cc                         | LENGTH - WITH HANDLES                      | 1,198 mm (47.2 in.)                        |
| STARTING SYSTEM                          | ELECTRIC / RECOIL              | WIDTH - WITHOUT HANDLES AND WHEELS         | 539 mm (21.2 in.)                          |
| LOW LEVEL OIL ALERT <sup>TM</sup> SYSTEM | STD. (LED DISPLAY)             | WIDTH - WITH WHEELS                        | 700 mm (27.6 in.)                          |
| AUTO THROTTLE                            | ECO-THROTTLE <sup>™</sup> STD. | HEIGHT - WITHOUT LIFT-HOOK                 | 721 mm (28.4 in.)                          |
| REMOTE START CAPABILITY                  | OPTIONAL                       | HEIGHT - WITH LIFT-HOOK                    | 821 mm (32.3 in.)                          |
|  |                                | DRY WEIGHT                                 | 118.1 kg (260.4 lb) (INCLUDING<br>BATTERY) |
|  |                                |  |  |

COLD CLIMATE TECHNOLOGY

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

@/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.