



HRR216VKC

- Honda GCV160 OHC engine
- Self-propelled with variable speed transmission and Smart Drive™ control
- Heavy duty 53 cm (21 in.) steel deck
- Residential lawn mowing



SPECIFICATIONS

ENGINE TYPE	4-Stroke, OHC	DECK TYPE (STANDARD)	Rear bag, mulcher, rear discharge
Honda ENGINE MODEL	GCV160	CUTTING HEIGHT RANGE	2.9 - 10 cm (1.125 - 4 in)
DISPLACEMENT	160 cc (9.8 CID)	CUTTING HEIGHT ADJUSTMENTS	6 positions
IGNITION SYSTEM	Transistorized	WHEEL SIZE	20 cm (8 in)
STARTING SYSTEM	Recoil starter (Handle mounted)	WHEEL MATERIAL	High impact plastic
ZONE START SAFETY SYSTEM	Standard	WHEEL BEARING	Ball bearing on rear wheels
AIR CLEANER	Paper cartridge	GRASS BAG	Standard
LUBRICATION SYSTEM	Forced splash	BAG CAPACITY	85.0 L (2.4 bushels)
OIL CAPACITY	0.55 L (19.4 fl. Imp. oz)	DISCHARGE CHUTE	Rear discharge chute standard
RECOMMENDED FUEL	Regular unleaded gasoline (87 Octane)	MULCHING CAPABILITY	Standard
FUEL CAPACITY	0.93 L (32.7 fl. Imp. oz)	MULCHING PLUG/COVER	N/A
FUEL CONSUMPTION (APPROXIMATE)***	1.10 L/hr (0.24 Imp. gal/hr)	MULCHING SYSTEM	MicroCut System™
CHOKE SYSTEM	Automatic	DRY WEIGHT	37.2 kg (82.0 lb)
TRANSMISSION	Variable speed (VST) with multi-position Smart Drive™	BLADE (S)	Standard (Twin-blades)
GROUND SPEED(S)	0 - 6.44 km/h (0 - 4.00 mph)	BLADE CONTROL SYSTEM	Flywheel brake
DECK SIZE	53 cm (21 in)	STANDARD CONFIGURATION	3 in 1: Mulch, bag, discharge
DECK MATERIAL	Steel (16 gauge)	OPTIONAL CONFIGURATION	4 in 1 with optional leaf shred
DECK GUARDS (MATERIAL)	N/A	VERSAMOW™ SYSTEM	N/A

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.