
## **HS720C**

- Single-stage, semi-self propelled auger drive, clears a 20 in/51 cm width, 12 in/30.5 cm high
- Honda premium residential engine GC190, 4stroke, overhead cam (OHC)
- SnowDirector chute control for easy control of distance and direction
- · Residential snow removal



40.3 kg (88.8 lb)

SPECIFICATIONS			
Discharge Type	Single stage	Clearing Snow Volume Capacity (Approximate)1	Up to 45 metric tons/hr (50 tons/hr)
Axle Type	Wheel	Engine Type	4-stroke; OHC; single cylinder
Drive Type	Auger assist		GC190
Speeds	N/A	Honda Engine Model	
Maximum Ground Speed	N/A	Displacement	187 cc (11.4 CID)
Clearing Width	50.8 cm (20.0 in)	Ignition System	Transistorized magneto
Intake Housing Height	30.5 cm (12.0 in)	Recoil Starter	Standard
Auger Diameter	23.0 cm (9.1 in)	Electric Starter	N/A
		<b>Lubrication System</b>	Forced splash
Auger Type	Rubber edge	Oil Capacity	0.58 Litre (20.4 fl. Imp. oz)
Auger Drive	Belt	Recommended Fuel	Regular unleaded gasoline (87 Octane)
Auger Height Adjustment	Scraper bar		
Chute Rotation	Remote manual lever	Fuel Capacity	1.1 Litre (38.7 fl. Imp. oz)
Chute Turning Radius	204°	Operational Time per Tankful 2	1.0 hour
Deflection Control	Remote manual lever	Wheel/Tire Size	17.8 cm (7.0 in)
Chute Material	Steel	Overall Length	126.0 cm (49.6 in)
Maximum Throw Distance1	10 m (32.8 ft)	Overall Width	53.0 cm (20.9 in)
		Overall Height	103.0 cm (40.6 in)

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

**Dry Weight** 

@/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.