

Teagle

spir@mix Concrete Mixer



Spir@mix 200H Holds 50 kg of cement and a 6:1 mix of aggregate

EASY LOADING through the wide mouth of the drum.

EASY UNLOADING - the drum rotates in one direction for mixing and in the opposite direction for unloading. Hydraulic motor drive - easily controlled from the tractor seat via the external services spool valve.

GOOD MIX - the deep spirals, needed to give a good unloading action, also give a quick and thorough mix.

GOOD UNLOADING HEIGHT - because the drum does not tip to unload, the discharge height is always good.



Spir@mix 100H Holds 25 kg of cement and a 6:1 mix of aggregate



	Model 100H	Model 200H
Drum Volume	280 litres (10 cu. ft.)	560 litres (20 cu. ft.)
Approx. Mix Volume	140 litres (5 cu. ft.)	280 litres (10 cu. ft.)
Loading Height to Drum Lip	37 cm. (15 in.)	57cm. (22 in.)
Weight Empty	118 kg. (262 lb.)	190 kg. (420 lb.)
Approx. Laden Weight	430 kg. (950 lb.)	815 kg. (1790 lb.)
Drum Diameter	65 cm (25 in.)	82 cm. (32 in)
Drum Length	89 cm. (35 in.)	111 cm. (43 in.)
Mounting	Cat 1/2 Linkage	Cat 2 Linkage
Min. Tractor Size	15 kW (20 HP)	40 kW (50 HP)

The Company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice

BLACKWATER, TRURO, CORNWALL TR4 8HQ, UK.

Tel **+(44) 01872 560592** Fax **+(44) 01872 561166**

E-mail **sales@teagle.co.uk** Web **www.teagle.co.uk**

Teagle