



300U

Forestry mulcher for special built hydraulic or PTO driven Prime Movers with power range between 200 and 400 HP.

Standard equipment: double side transmission, hydraulic hood, adjustable skids.

Options: customized hydraulic or PTO transmission, pushing frame, hydraulic pushing frame, customized attachment plate, teeth on hydraulic hood, possibility to have the rotor equipped with tooth type "B" or tooth type "C" or "C/SD".



300U

Model	Power HP Min - Max	Requirements		Working width inches	Overall width inches	Weight lbs rotor type C	Weight lbs rotor type B	Grinding diameter inches (max)	Teeth q.ty	
		Flow gal/min Min - Max	Pressure PSI Min - Max						B+C/SS	C+C/SS
300/U - 200	200 - 400	100 - 150	3500 - 5000	81	95	5689	4410	16	80+2	44+2
300/U - 225	200 - 400	100 - 150	3500 - 5000	91	105	5887	6549	16	88+2	50+2
300/U - 250	200 - 400	100 - 150	3500 - 5000	100	114	6086	6615	16	102+2	56+2

The data refers to the machine without options. Technical datas for models with mechanical transmission upon request.



Tooth type B



Tooth type C



Tooth type B/SR (option)



Tooth type C/SD (option)



Tooth type C/SS (side scraper)