

Snowblower

MODEL	5010	6010	6610	7420	8420	8420G	9620Q	1080C
Cutting width	50"	60"	66"	74"	84"	84"	96"	108"
Cutting height	25"	25"	25"	30"	30"	30"	36"	41"
Replaceable cutting edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Yes
Fan	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade
Fan diameter	20"	22"	22"	24"	24"	24"	34"	36"
Replaceable fan housing	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7 gauge
Drive fan	540 RPM open gear	540 RPM open gear	540 RPM open gear	540 RPM open gear	540 RPM open gear	540 RPM oil bath gearbox	540 RPM oil bath gearbox	1000 RPM oil bath
Auger diameter	13"	15"	15"	15"	15"	15"	15" (dual)	15" (dual)
Auger drive	#50 chain	#50 chain	#50 chain	#50 chain	#50 chain	#50 chain	#60 chain	#80 chain
Spout rotator - manual (hand crank) - hydraulic	Standard Optional	Standard Optional	Standard Optional	Optional Standard	Optional Standard	Optional Standard	Optional Standard	N/A Standard
Spout deflector - manual (6 position) - hydraulic	Standard Optional	Standard Optional	Standard Optional	Standard Optional	Standard Optional	Standard Optional	Standard Optional	N/A Standard
Skid shoes	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable
Hitch category	Cat. I standard	Cat. I standard	Cat. I standard	Cat. I standard Cat. II bushings	Cat. I & II std Cat. II Q.H. std Cat. III Q.H. narrow	Cat. I & II std Cat. II Q.H. std Cat. III Q.H. narrow	Cat. II std Cat. III Q.H. std Cat. III Q.H. narrow	Cat. II std Cat. III Q.H. std Cat. III Q.H. narrow
Hitch adjustment	4 position	4 position	4 position	2 position	2 position	2 position	Fixed	2 position
Tractor requirement	15 - 30 hp	20 - 40 hp	22 - 40 hp	40 - 70 hp	60 - 90 hp	60 - 90 hp	90 - 125 hp	120 - 180 hp
Weight	422 lb	470 lb	515 lb	756 lb	848 lb	878 lb	1243 lb	2398 lb