

# Stump Grinder

MODEL	2628	3633	2628H
Hitch	Cat. I	Cat. I / II	Universal skid steer
Overall length	75"	80"	72"
Drive system protection	Slip clutch	Slip clutch	System pressure
Gearbox rating / ratio	60 hp / 1:1.5	100 hp / 1:1.46	60 hp / 1:1.5
Cutting wheel construction	Welded 2 piece laminated steel		
Cutting wheel thickness	3/4"	3/4"	3/4"
Cutting wheel diameter	26"	36"	26"
Cutting wheel speed @540 PTO RPM	810 RPM 5,515 ft/min	788 RPM 7,430 ft/min	810 RPM 5,515 ft/min
Number of teeth	33	42	33
Cutting teeth construction	Carbide steel bolt in	Carbide steel bolt in	Carbide steel bolt in
Cut height above ground	18"	18"	18"
Cut depth below ground	10"	15"	10"
Max. cut depth per pass	5"	8"	5"
Max. horizontal cut	28"	33"	28"
Swing arc	45°	45°	45°
Min. power / flow required	22 PTO hp	45 PTO hp	15 GPM
Max. power / flow	50 PTO hp	100 PTO hp	25 GPM
Drive system	PTO / Series 5	PTO / Series 6	Hydraulic
PTO speed	540 RPM	540 RPM	540 RPM @ 19.4 GPM
Weight	660 lb	880 lb	757 lb