

# NUTRI-PLACER 920 PULL-TYPE APPLICATOR

**CASE IH**  
AGRICULTURE



# NUTRI-PLACER 920 PULL-TYPE LIQUID FERTILIZER APPLICATOR

## Features

- 23 or 25 rows for big productivity and to match 24-row planters
- Outer wings can be folded to 15 coulters to match 16-row planters
- High Capacity Jack Stand w/ 10" x 10" footprint
- Narrow Hitch for tight turning radius
- X-Wing Frame Fold for narrow transport width and low transport height
- Forward mounted applicator frame for easy viewing of applicator
- 5 section boom application capable
- Applicator frame mounted to parallel arms for level lifting and lowering for better fertilizer placement
- 5 section flex with active down pressure for better fertilizer placement
- Greaseless poly bushings in wing pivots for low maintenance
- Frame strength and smooth gusseting for stress relief and long toolbar life
- 3" Tank Fill easy to reach and away from any electronics
- 1650 gallon tank for more time in the field and less time filling
- Low center of gravity tank for more stability
- Front and Rear tank level sight gauge
- Wash tank conveniently mounted near product fill area.
- Hydraulic drive pump for better rate control and easier rate adjustment
- Mount provided for section and rate control valves
- High Capacity 420/80R46 tires for larger footprint and less compaction

NUTRI-PLACER 920 PULL-TYPE APPLICATOR	60 FT. (18.3 M)
Frame Style	Pull-Type
Row Spacing	30 in. (76 cm)
Number of Coulters	23 or 25
Tank Capacity	1,650 gal. (6 246 L) poly tank
Fold Type	Hydraulic X-Fold
Transport Height	13 ft. 4 in. (4.1 m)
Transport Width	16 ft. 8 in. (5.1 m)
Wing Flex	5 section (inner wing - 7 degrees up/7 degrees down; outer wings - 7 degrees up/7 degrees down)
Tire Size	Singles Qty. 2 - 420/80R46 w/ 10-bolt hub)
Wheel Spacing	120 in. (3 m)
Gauge Wheels	Qty. 4 - 20.5 x 8 pin adjust
Hitch	Category 4 clevis
Pull-Frame Tubing	Double 4 in. x 8 in.
Coulter Frame Tubing	Dual rank mainframe 4 in. x 7 in. tubing - center 19 rows; Single 4 in. x 6 in. tube - remaining rows
Crop Clearance to Tank Frame	33 in.
Crop Clearance to Toolbar Frame	24 in.
Row Unit	Coulters w/ Injectors or Knives
Wash Tank Capacity	7 gal.
Weight Empty	16,390 lbs.
Tongue Weight	6,310 lbs.
Minimum Hp Requirement	240 Engine hp
Options	Hydraulic driven pump



PRODUCT SPECIFICATIONS

SAFETY NEVER HURTS!<sup>™</sup> Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used. ©2012 CNH America LLC. All rights reserved. Case IH is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. Printed in U.S.A. [www.caseih.com](http://www.caseih.com)