

CX Series Conventional Auger

| MODEL | CX841 | CX851 | CX861 | CX1041 | CX1051 | CX1061 |
|------------------------------------------|--------|--------|--------|--------|---------|--------|
| Recommended Horsepower (Engine) | 16 | 20 | 24 | 28 | 32 | 38 |
| Capacity (bu/hr) ¹ | - | - | - | 4400 | 4400 | 4400 |
| Rim Size | 15" | 15" | 15" | 15" | 15" | 15" |
| Hub Type | 5 bolt | 5 bolt | 5 bolt | 5 bolt | 5 bolt | 5 bolt |
| Fuel Tank Capacity (US Gal) ² | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 |
| Lower Tube Reach ³ | 12' 2" | 13' 0" | 13' 2" | 10' 5" | 12' 10" | 13' 0" |
| Maximum Spout Height | 28' 3" | 35' 2" | 42' 0" | 28' 3" | 32' 8" | 39' 3" |

¹ The fuel tank is not yet approved by the EPA for use in the USA.

¹ Capacity will vary with field conditions. Tested on wheat, - 12.5% moisture, using the CX1041 model.

² Fuel tanks are supplied with engine configuration only.

³ Tube reach is measured along the auger tube, from the tip of the intake guard to the gear box on the engine drive configurations.

| AUGER MOVER FEATURES |
|----------------------------------------------|
| Power Steering |
| Fuel Tank Capacity - 6.5 US Gal ² |
| Central Control Location |
| Mover Mounts to Undercarriage only |
| Rear Wheel(s) Lift for Transport |

¹ The fuel tank is not yet approved by the EPA for use in the USA.

² Fuel tanks are supplied with engine configuration only.