

Backsaver Auger - 10 / 12

MODEL	1062	1072	1082	1262	1272	1282	1292
Size	10" x 62'	10" x 72'	10" x 82'	12" x 62'	12" x 72'	12" x 82'	12" x 92'
Tubing	12 gauge	12 gauge	12 gauge	12 gauge	12 gauge	12 gauge	12 gauge
Flighting	1/4" flighting in main auger, 5/16" flighting in swing away auger						
Flighting shaft	12 gauge, 2-3/8" diameter			11 gauge, 2-7/8" diameter			
Undercarriage tubing	2" x 4" x 11 ga.		2" x 4" x 3/16"			2" x 4" x 1/4"	
Lift arms, upper and lower	2" x 3" x 11 ga.		2" x 4" x 11 ga.	4" x 6" x 3/16"			
Bridging cable	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Wheels and hubs	15" w/6 bolt automotive type hubs and bearings						
Swing auger drive, w/extended life bearings	540 rpm 35 series CV PTO			540 rpm 35 series CV PTO		540 rpm 55 series CV PTO	
Hopper dimensions	32" x 60"	32" x 60"	32" x 60"	48" x 60"	48" x 60"	48" x 60"	48" x 60"
Hopper height from ground*	10-3/4"	10-3/4"	10-3/4"	10-3/4"	10-3/4"	10-3/4"	10-3/4"
Tractor requirements - min PTO hp (w/540 rpm) - approx. hyd. req. for lift	48 hp 1500 PSI	54 hp 1500 PSI	62 hp 1500 PSI	62 hp 1500 PSI	72 hp 1500 PSI	82 hp 1500 PSI	92 hp
Wheel track	108"	114"	135"	108"	125.5"	133.5"	133.5"
Height, discharge (max)	43' 6"	48'	58'	43' 6"	52'	56' 6"	62'
Height, transport	12' 6"	13' 6"	15' 6"	12' 6"	11' 6"	12'	13' 6"

* standard hopper