

Rotary Tiller

SERIES	25			45		65	
	MODEL	236	245	254	4560	4572	6572
Tillage width	36"	45"	54"	55"	69"	68"	77"
Overall width	46-1/2"	54-1/2"	66-1/2"	66"	78"	78"	88"
Tractor requirement	12 - 18 hp	14 - 22 hp	18 - 25 hp	25 - 40 hp	30 - 45 hp	45 - 55 hp	55 - 65 hp
3-point hitch	Category I			Category I		Category I, optional fit Category II	
Gearbox	Heavy-duty oil bath (540 RPM)			Heavy-duty oil bath (540 RPM)		Heavy-duty oil bath (540 RPM)	
Chain in oil bath	#80H	#80H	#80H	#80H	#80H	#100H	#100H
Rotor speed RPM	239 RPM	239 RPM	239 RPM	203 RPM or 865 ft/min		196 RPM or 880 ft/min	
Sideshift	n/a	n/a	n/a	6-3/4"	8-1/2"	15"	n/a
PTO shaft	Slip clutch			Slip clutch		Slip clutch	
Tine size	1/4" x 2-1/4"	1/4" x 2-1/4"	1/4" x 2-1/4"	1/4" x 2-1/4"	1/4" x 2-1/4"	5/16" x 3-1/4"	5/16" x 3-1/4"
No. of tines/No. of flange	16/4	20/5	24/6	24/6	32/8	42/7 (option 28/4)	48/8 (option 32/4)
No. of tines per flange	4	4	4	4	4	6 (opt. 4)	6 (opt. 4)
Skid shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Weight	385 lb	418 lb	477 lb	613 lb	688 lb	906 lb	968 lb