

NUTRI-PLACER 2800 SIDEDRESS APPLICATOR Specifications



Model Nutri-Placer 2800

MODELS	500 or 850 GALLON	1,300 GALLON
Tank capacity	500 or 850 gallons (1893 or 3218 L)	1,300 gallons (4921 L)
Coulters	7, 9, or 11 at 30 in. (76 cm) spacing	11, 13, or 15 at 30 in. (76 cm) spacing
Working widths	17 ft. 6 in. – 27 ft. 6 in. (5.3 – 8.4 m)	27 ft. 6 in. – 37 ft. 6 in. (8.4 – 11.4 m)
Transport dimensions	12 ft. 4 in. (3.8 m) width x 9 ft. 8 in. (3.0 m) height – max.	12 ft. 6 in. (3.8 m) width x 13 ft. (4.0 m) height
Tire size	8-bolt hub with 14Lx16.1 12PR	10-bolt hub with 420/80R46
Wheel spacing	Adjustable: 62, 72, 76, and 80 in. (157, 183, 193, and 203 cm) Fixed: 120 in. (305 cm)	Adjustable: 120, 144, and 156 in. (305, 366, and 396 cm)
Gauge wheels	NA	Pin adjust
Frame tubing	4 x 4 in. (10 x 10 cm)	4 x 8 in. (10 x 20 cm) frame & hitch; 4 x 6 in. (10 x 15 cm) toolbar
Constant-balance tongue weight	< 1,000 lb. (454 kg) with 7 coulters < 1,200 lb. (544 kg) with 11 coulters	< 2,500 lb. (1134 kg) with 15 coulters
Clevis	Combination single or double	Combination single or double
Ground drive	Dyna-Trak tire; stainless-steel drive chain; John Blue 1- or 2-piston pump	Dyna-Trak tire; stainless-steel drive chain; John Blue 2-piston pump
Flashing & warning tail lamps	Standard	Standard
Wash tank	NA	Standard
Wing-fold hydraulics	Standard	Standard
Active hydraulics	NA	Standard