



UMH UMH/S

Forestry mulcher with fixed teeth rotor for tractors between 110 and 390 HP.

Standard equipment: PTO driveshaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skids, hydraulic top link, self ranging system of the PTO driveshaft/gearbox.

Options: mechanic or hydraulic push frame, special skids to go underground, rake teeth on hydraulic hood, option of rotor equipped with tooth type "C/HD" or type "A/HD".

Notes: For the correct usage, creeper gear transmission and reversible driving console are recommended.



UMH

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight with rotor		Grinding diameter inches (max)	Teeth q.ty	
	min	max				type C lbs	type A lbs		type A+C/SS	type C+C/SS
UMH 150	110	150	1000	63	81	6019	6725	16	60+2	32+2
UMH 175	130	150	1000	72	91	6416	7122	16	68+2	36+2
UMH 200	160	280	1000	82	100	7364	8136	16	78+2	40+2
UMH 225	180	280	1000	91	110	7761	8533	16	88+2	44+2
UMH 250	200	280	1000	101	119	8158	8930	16	96+2	48+2

UMH/S

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight with rotor		Grinding diameter inches (max)	Teeth q.ty	
	min	max				type C lbs	type A lbs		type A+C/SS	type C+C/SS
UMH/S 225	180	390	1000	91	110	8291	8842	16	88+2	44+2
UMH/S 250	200	390	1000	101	119	8621	9415	16	96+2	48+2

Data refers to the machine without options.



Tooth type A




Tooth type C



Tooth type A/HD (option)



Tooth type C/HD (option)



Tooth type C/SS (side scraper)