



UMM/S UMM/S/HP

Forestry mulcher with fixed teeth rotor for tractors between 130 and 300 HP.

Standard equipment: PTO driveshaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skirts, hydraulic top link, self ranging system of the PTO drive shaft/gearbox. UMM/S/HP stronger transmission for tractors up to 300 HP.

Options: mechanic or hydraulic push frame, special skirts to go underground, rake teeth on hydraulic hood, option of rotor equipped with tooth type "C/HD".

Notes: For the correct usage, creeper gear transmission and reversible driving console are recommended.



UMM/S

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight with rotor		Grinding diameter inches (max)	Teeth q.ty	
	min	max				type C lbs	type B lbs		type B/3+C/SS	type C+C/SS
UMM/S 200	130	240	1000	81	98	5865	6549	14	72+2	44+2
UMM/S 225	140	240	1000	91	107	6130	6813	14	80+2	50+2
UMM/S 250	150	240	1000	100	117	6394	7078	14	92+2	56+2

UMM/S/HP

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight with rotor		Grinding diameter inches (max)	Teeth q.ty	
	min	max				type C lbs	type B lbs		type B/3+C/SS	type C+C/SS
UMM/S/HP 200	130	300	1000	81	98	5976	7056	14	72+2	44+2
UMM/S/HP 225	140	300	1000	91	107	6240	6924	14	80+2	50+2
UMM/S/HP 250	150	300	1000	100	117	6505	7188	14	92+2	56+2

Data refers to the machine without options.



Tooth type B/3



Tooth type C



Tooth type C/HD (option)



Tooth type C/SS (side scraper)