

## WR101 CARTED WHEEL RAKE





SPECIFICATIONS	8 Wheel	10 Wheel	12 Wheel
RAKING COMPONENTS			
Number of Finger Wheels	8	10	12
Finger Wheel Diameter	55 in. (1.4 m)	55 in. (1.4 m)	55 in. (1.4 m)
Teeth per Wheel	40	40	40
Finger Wheel Hub Bearing Type	Tapered Roller - Greasable	Tapered Roller - Greasable	Tapered Roller - Greasable
Minimum Working Width	16 ft. 4 in. (5.0 m)	19 ft. (5.8 m)	21 ft. 8 in. (6.6 m)
Maximum Working Width	19 ft. (5.8 m)	22 ft. (6.7 m)	25 ft. 7 in. (7.8 m)
Minimum Windrow Width	3 ft. (0.9 m)	3 ft. (0.9 m)	3 ft. (0.9 m)
Maximum Windrow Width	6 ft. 7 in. (2.0 m)	6 ft. 7 in. (2.0 m)	6 ft. 7 in. (2.0 m)
DIMENSIONS			
Weight - lb. (kg)	1500 (675 kg)	1630 lb. (740 kg)	1830 lb. (830 kg)
Transport Wheel size	205/75-15	205/75-15	205/75-15
Overall Length- Transport	19 ft. (5.8 m)	19 ft. (5.8 m)	22 ft. (6.7 m)
Transport Height - Maximum	8 ft. 6 in. (2.6 m)	8 ft. 6 in. (2.6 m)	8 ft. 6 in. (2.6 m)
Overall Transport Width	10 ft. 2 in. (3.1 m)	10 ft. 2 in. (3.1 m)	10 ft. 2 in. (3.1 m)
TRACTOR REQUIREMENTS			
Minumum Tractor Horsepower Required	30 HP (22.3 kW)	30 HP (22.3 kW)	50 HP (36.7 kW)
Tractor Hydraulic System Requirements	1 DA w/ float	1 DA w/ float	1 DA w/ float

STAI	NDARD EQUIPMENT
	Clearance Wheel ne Design
	stable Wheel ne Suspension
	zontal Wheel ne Transport Position
Safe	ty Tow Chain

## **OPTIONAL EQUIPMENT** Center Kicker Wheel Hydraulic Frame Angling Kit 8 to 10 Wheel Conversion Kit



Safety Never Hurts!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

Case IH is a registered trademark of CNH America LLC.

Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Availability of some models and equipment builds vary according to the country in which the equipment is used.