

FOR FRUIT GROWERS

WILL FOLLOW YOU EVERYWHERE



TRACKING AXLE:

It permits to continue spraying uniformly on sharp turns with no need to disengage the PTO, avoiding unecessary maneuvers. PTO shaft with safety guard.



The Arbus 1000 has a 2.75 m (9ft) turning radius so you never cut corners... versatile attachments make it perfect for orchards, vineyards and row crops.





OPTIONAL ACCESSORY

The Arbus 1000 can be equipped with 2 hoses and guns for localized spot spraying.



SPECIFICATIONS

DIMENSIONS

Length 3.80 m (12' 6") Width 1.34 m (4' 5") Height 1.20 m (3' 11")

TRAILER

 Track width
 1.15 m (3' 9")

 Tires
 7.35/14 (6 ply)

 Tire pressure
 2.5 kg/cm² (35 psi)

 Clearance
 0.25 m (10")

NOZZLES

Type JA-2 Material Alumina Feature Adjustable

Working pressure Max: 21 kg/cm² (300 psi)

Number 18

TANK

Capacity 1000 I (265 gal)

Material Fiberglass with smooth external finish

FILTER

Model FVS 101

PRESSURE CONTROL

Pressure gauge Glycerin filled

SPRAY CIRCUIT

Spray tubing Stainless steel
Level indicator Hose attached to tank

Agitator Mechanical

Working speed Up to 6 km/h (3.75 mph)
Performance Up to 20 ha/dia (49 acres/day)
Applications Fruit crop, medium and low

nursery plants.

FEATURES

VERTICAL AIR DIRECTIONAL FLAP

PUMP

PUMPING CAPACITY WORKING PRESSURE POWER CONSUMPTION

AXLE

BYPASS VALVE

WEIGHT: FIXED AXLE

TRACKING TRAILER

PUMP JP - 75

JP-75

OPTIONAL

75 l/min (20 gpm) at 540 rpm

28 kg/cm² (400 psi)

5.3 HP at 28 kg/cm² (400 psi)

Fixed/Tracking

2 way valve

525 kg (1157 lb) 540 kg (1190 lb) OPTIONAL

JP-100

100 l/min (27 gpm) at 540 rpm

PUMP JP - 100

28 kg/cm² (400 psi)

7.0 HP at 28 kg/cm² (400 psi)

OPTIONAL

Fixed/Tracking 2 way valve

535 kg (1180 lb) 550 kg (1210 lb)

FAN: PULLEY DIAMETER

RPM

AIR VOLUME AIR SPEED

TOTAL POWER CONSUMPTION: with JP-75 PUMP

with JP-100 PUMP

STANDARD

89 mm (3.5 in) 2000

9.7 m³/s (20,550 cfm) 151 km/h (94 mph)

21.5 HP at 28 kg/cm² (400 psi) 23.5 HP at 28 kg/cm² (400 psi) 100 mm (4 in)

1800

8.7 m³/s (18.434 cfm) 136 km/h (85 mph)

17.5 HP at 28 kg/cm² (400 psi) 19.0 HP at 28 kg/cm² (400 psi)



MÁQUINAS AGRÍCOLAS JACTO S.A.

Rua Dr.Luiz Miranda, 1650 17580-000 - Pompéia- SP - Brasil Tel.: (14) 3405 2100 - Fax (14) 452 1916 e-mail: export@jacto.com.br

A light, robust and versatile sprayer designed for small and medium size trees.




LOW PROFILE

Height: 1.2 meters (4ft). Meets the requirements of different types of orchards.



NOZZLES

Stainless steel tubing mounted with 18 adjustable ceramic nozzles with individual shut off valve.



PUMP

High-pressure, cast iron piston pump with ceramic cylinders. Highly resistant to abrasion.



PRESSURE GAUGE Glycerin-filled for longer life and precision.



FILTER

FAN

Equipped with switch

off device to reduce

power consumption

when use of fan is not required as for gun spraying. Reinforced frame to protect against impacts on the soil.

High-volume (polypropylene) filter with stainless steel screen and shut off valve to facilitate cleaning.

