



Load it up. This versatile loader tractor gets after ANYTHING.

# It has a nose for what you want it to do.

Visibility is key in loader work. Our MF5609 and MF5610 each offer a new sloped nose to improve sightline down the hood and beyond the bucket. The Visio roof further improves forward visibility, even at full loader height.



The larger, 6-post cab design provides a sweeping 360° view, as well as a roomier, more comfortable and productive workspace.



Powerful and maneuverable, these tractors are multi-taskers, even in close quarters. The proven Dyna-4™ transmission has many new features, including AUTO-DRIVE, which automatically and smoothly shifts gears as if driving a car.

Model	5609	5610
PTO power @ 2200 RPM HP (kW)	70 (52)	75 (56)
Engine power HP (kW)	90 (67)	100 (75)
Engine make/model	33 AWI HD by AGCO Power	
Cylinders/displacement L (CID)	3-cylinder/3.3 (201)	
Aspiration/charge cooling	Turbocharged & intercooled	
Fuel system	Common rail direct injection	
Emissions control	External Exhaust Gas Recirculation (EGR), Diesel Oxidation Catalyst (DOC)	
Fuel capacity gal. (L)	42 (160)	
<b>Transmission</b>		
Type: standard	Dyna-4 transmission with speed matching; AUTO-DRIVE is optional	
Speeds	4 gears, 4 ranges, 16 total speeds	
Shuttle	Electro hydraulic via LH 3-function control lever or optional RH factory loader joystick	
Creeper	Optional 14:1 reduction	
<b>Rear 3-point Hitch</b>		
Type/ASAE category	Electronic linkage control with lower link draft sensing/Cat II	
Lift capacity @ 24" lbs. (kg)	7,100 (3,220)	
<b>4wd Front Axle</b>		
Type	Center Drive with planetary reduction	
Drive engagement	Electro hydraulic	
<b>Rear Axle</b>		
Type	Flange with internal wet disc brakes	
Differential lock	Fully locking electro hydraulic	
Braking	Independent, internal wet multi-disc brakes	
<b>Power Take Off (PTO)</b>		
Type	Independent, electronically engaged	
Speeds	540/540e	540/540e/1000
<b>Hydraulics</b>		
System type	Open center	
Standard flow at remotes gpm (Lpm)	15 (57)	
Optional flow at remotes gpm (Lpm)	26 (100) with Twin Flow System	
Rear remote valves	2 standard, up to 4 available	
Loader joystick option	Integrated factory loader joystick with shuttle control and mid valves	
<b>Operator's Area</b>		
Type of operator's area	6-post cab, twin doors, flat deck	
Steering / seat	Adjustable steering/mechanical or air suspended seat	
Cab suspension	Optional mechanical system	
<b>Dimensions</b>		
Height over cab in. (mm)*	108.5 (2,755)	
Overall length in. (mm)	167.5 (4,253)	
Wheelbase in. (mm)	97.1 (2,467)	
Min. width at fenders in. (mm)	79.3 (2,013)	
Weight lbs. (kg)	2wd: 7,826 (3,550) /4wd: 8,378 (3,800)	

\*Height for Standard Cab, no Susp, flat floor and 16.9R34 tires