

# Seed Runner model 5000 Larger capacity, greater reach for larger, faster planters

The Seed Runner® model 5000 is designed specifically to keep pace with today's largest and fastest planters. The model 5000 features a 500-seed-unit capacity and a two-stage conveyor — a low-profile intake coupled with a tubular loading conveyor — for 90 inches of vertical-height adjustment and 24 feet of reach for quick, convenient and gentle unloading.

## **Unverferth** Bulk-Seed Handling

### Seed Runner model 5000:

### 3-in-1 seed-handling versatility for the largest planters and drills

The model 5000 Seed Runner® seed tender features a dual-compartment design with large, conveniently placed windows, LED fill lights and work lights for easily monitoring seed loading and unloading, day or night.

One-person operation is achieved with the standard 7-function wireless remote with LCD scale readout that controls engine and conveyor operations, including the ability to pivot the conveyor 180° for self-loading and even reaches under grain trailers with ag hoppers. The conveyor can also be positioned parallel to the tender for transferring seed from one container to another.

#### That's 3-way versatility and triple the value – loading, unloading and transferring.

- Innovative two-stage conveyor design for quick, gentle handling of all seed types; crescentshaped cleats on intake conveyor belt gently transfers seed from the tank to a 10-inch diameter tube with patent-pending 15-inch belt featuring cupped rows of offset cleats
- Unloading speed up to 45 bushels per minute for a quick return to planting
- Conveyor powered by 6-cubic-inch, top-mounted hydraulic motor to keep the belt tight for smooth operation and longer belt life
- Electronic conveyor engagement delivers gentle starts and quickly accelerates to operating speed for enhanced belt performance
- Rollover tarp made of 18-ounce canvas and features cable tensioning for quick, smooth operation
- Heavy-duty undercarriage with gooseneck hitch, tandem 16,000 lb. axles, spring-ride suspension and dual wheels for greater maneuverability
- 4-wheel electric brakes, transport chains, reflective striping, LED lighting – including clearance lights – for safer road travel
- Trademarked ivory and tan finish with silicone-sealed seams for longlasting finish
- Hydraulics powered by reliable, electric-start Honda engine producing 690 cc (22 gross HP) for optimum performance

#### **Options:**

- Scale packages featuring an easy-to-see LCD display, even at a distance
- T&G applicator for accurately applying seed lubricants for enhanced planter performance
- Spare wheel and tire for transport security
- Electric-operation for tarp
- · Electric-over-hydraulic-operated jack
- Telescopic 3-stage downspout for reach of up to 50'

See your nearest Unverferth dealer today or <u>umequip.com</u> for complete details on the 5000 and all Seed Runner tender models.





#### **Model 5000** specifications

Overall length – transport	32'5"
Overall width – transport	8'6"
Overall height – transport	11'11"
Overall load height	11'
Box length	16'8"
Box width	8'6"
Box height	9'6"
Conveyor length past the hitch	4'
Undercarriage deck height	2'4"
Undercarriage under-frame clearance	1'1"
Conveyor height in transport position	8'10"
Conveyor maximum unload height	16'6"
Conveyor reach at maximum unload height	16'3"
Conveyor minimum unload height	8'8"
Conveyor reach at minimum unload height	19'9"
Approximate empty weight	11,150 lbs.
Loaded tongue weight	6,700 lbs.
Lighting connector	7-pin flat
Standard downspout reach (4' flex spout)	40'
Maximum downspout reach (3-stage spout)	50'

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



P.O. Box 357 • Kalida, Ohio 45853 (419) 532-3121 • unverferth.com

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2015 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

® ™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH. Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada. U.S. Patents 7,690, 449; 8,221,047 and 8,967,940. Additional U.S. and foreign patents pending.



